

Appl. No. 09/271,411
Amdt. dated February 15, 2008
Reply to Office Action of October 18, 2007

PATENT

RECEIVED
CENTRAL FAX CENTER

FEB 15 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1-59. (canceled)

60. (Previously presented) A method for analyzing a sample, the method comprising the steps of:

- a) introducing the sample into a device having:
 - i) a reaction chamber;
 - ii) a separation region;
 - iii) a transition region connecting the reaction chamber to the separation region, wherein the transition region has sufficiently low thermal conduction so that the transition region substantially thermally isolates the reaction chamber from the separation region; and
 - iv) at least one valve in the transition region;
- b) subjecting the sample to a reaction in the reaction chamber while the valve is closed, wherein the transition region substantially thermally isolates the reaction chamber from the separation region during the reaction;
- c) optically monitoring reaction products contained in the reaction chamber;
- d) determining if sufficient reaction products have been generated within the reaction chamber prior to injecting a sample plug into the separation region;
- e) opening the valve;
- f) injecting into the separation region the sample plug containing the reaction products;
- g) separating the reaction products in the separation region; and
- h) detecting the separated reaction products.

61. (Canceled)

Appl. No. 09/271,411

PATENT

Amdt. dated February 15, 2008

Reply to Office Action of October 18, 2007

62. (Previously presented) The method of claim 60, wherein the reaction comprises a nucleic acid amplification reaction, and wherein the reaction products comprise amplified nucleic acid.
63. (Previously presented) The method of claim 60, wherein the plug is injected into the separation region by electrophoretic injection.
64. (Previously presented) The method of claim 60, wherein:
- i) the device includes a body defining the reaction chamber, separation region, and transition region, and wherein the separation region comprises a separation channel;
 - ii) the device further includes at least two electrodes coupled to the body, the electrodes being positioned to induce electrophoretic flow, electroosmotic flow, or isoelectric focusing of the reaction products in the separation channel when a voltage difference is applied between the electrodes;
 - iii) the method further comprises the step of inserting the device into an instrument having electrical connections for applying the voltage difference between the electrodes and having at least one light source and detector for detecting the reaction products in the separation channel; and
 - iv) the steps of separating and detecting the reaction products comprise applying the voltage difference through the electrical connections in the instrument and detecting the reaction products using the at least one light source and detector.
65. (Previously presented) The method of claim 64, wherein the instrument further includes a heater for heating the reaction chamber, and wherein the step of subjecting the sample to the reaction comprises heating the reaction chamber with the heater.
66. (Previously presented) The method of claim 60, wherein:
- i) the device further includes a side channel connected to the transition region; and

Appl. No. 09/271,411

PATENT

Amdt. dated February 15, 2008

Reply to Office Action of October 18, 2007

- ii) the method further comprises the step of adding fluid to or removing fluid from the transition region through the side channel prior to, during, or after the step of injecting the sample plug into the separation region.
67. (Previously presented) The method of claim 60, wherein:
- i) the device further includes a side channel connected to the transition region; and
 - ii) the method further comprises the steps of adding reagents to the transition region through the side channel and mixing the reaction products with the reagents in the transition region prior to the step of injecting the sample plug into the separation region.
68. (Previously presented) The method of claim 60, wherein:
- i) the device further includes a side channel connected to the transition region; and
 - ii) the method further comprises the steps of adding buffer solution to the transition region through the side channel and injecting the buffer solution into the separation region prior to the step of injecting the sample plug into the separation region.
69. (Previously presented) The method of claim 66, wherein the device further includes at least a second valve for controlling fluid flow through the side channel, and wherein the method further comprises the step of opening and closing the second valve to control fluid flow through the side channel.
70. (Previously presented) The method of claim 60, wherein the reaction products are separated by electrophoresis.
71. (canceled).
72. (New) The method of claim 60, wherein the reaction products are separated by isoelectric focusing.